SS-CNP2/CRP2/MSP2

SERVICE MANUAL

Ver 1.0 2002. 02

US Model
Canadian Model
AEP Model
UK Model
E Model

SS-CNP2 SS-MSP2

- SS-CRP2 is the speaker section in HT-DDW740/DDW840.

- SS-CRP2 is composed of following models.

SS-CRP2	
FRONT and SURROUND speakers	SS-MSP2
CENTER speaker	SS-CNP2

SPECIFICATIONS

Speaker system	Full range, magnetically shielded
Speaker units	70 mm 100 mm cone type
Enclosure type	Bass reflex
Rated Impedance	8 ohms
Power handling capacity (Maximum input power)	100 W
Sensitivity level	85 dB (1 W, 1 m)
Frequency range	160 Hz – 20,000 Hz
Dimensions (w/h/d)	
SS-MSP2	Approx. 81 141 121 mm (3 1/4 5 5/8 4 7/8 inches)
SS-CNP2	Approx. 230 81 121 mm (9 1/8 3 1/4 4 7/8 inches)
Mass	
SS-MSP2	0.8 kg (1 lb 13 oz)
SS-CNP2	1.0 kg (2 lb 4 oz)

EXPLODED VIEW AND PARTS LIST





Ref. No.	Part No.	Description
1	A-4467-568-A	OVERALL ASSY (SILVER) (SS-CNP2)
1	A-4467-806-A	OVERALL ASSY (BLACK) (SS-CNP2)
2	A-4467-570-A	OVERALL ASSY (SILVER) (SS-MSP2)
2	A-4467-805-A	OVERALL ASSY (BLACK) (SS-MSP2)

SPEAKER SYSYTEM

9-873-476-01
2002B1600-1

© 2002.02

Sony Corporation
Home Audio Company
Published by Sony Engineering Corporation

SONY®

REVISION HISTORY

Clicking the version allows you to jump to the revised page.
Also, clicking the version at the upper right on the revised page allows you to jump to the next revised page.

Ver.	Date	Description of Revision
1.0	2002.02	New